

PLEIAD G4



	Pleiad G4 Flex	Pleiad G4 70	Pleiad G4 125	Pleiad G4 165	Pleiad G4 205	Pleiad G4 Wallwasher	Pleiad G4 Robust	Pleiad G4 Square	Pleiad G4 Surface 128	Pleiad G4 Surface 168	Pleiad G4 Track 128
--	----------------	--------------	---------------	---------------	---------------	----------------------	------------------	------------------	-----------------------	-----------------------	---------------------

Cut out dimensions (mm)	110	70	125	165	205	165	205	165x165	128	168	128
Ceiling thickness	5-50	5-50	5-50	5-50	5-50	0-35		5-50			
Max height	110	104	98	98	107	138	125	109	134	154	

Low Lumen (LL)	790-829	790-830	1200	1300	1675	900	1100	1300	1000	1600	1000
Medium Lumen (ML)				1800		1700	1600	1600	1400	2500	
High Lumen (HL)	1400	1280	2350	2800	2800	2500	2600	3500	2400	4500	2700
Extra High Lumen (EHL)				3700	5400						

Narrow Beam ~ 20°	●	●									
Medium Beam 40-50°	●	●	●	●	●			●	●	●	●
Wide Beam >70°			●	●	●		●	●	●	●	●

< UGR 19		●	●	●	●		●	●	●	●	●
< 3000 cd/m²		●	●	●	●		●	●	●	●	●

Luminaire body colour									white or black	white or black	white or black
Specular reflector						●					
Matt reflector		●	●	●	●	●	●	●	●	●	●
White reflector		●	●	●	●			●	●	●	●
Black reflector	●	●	●	●	●			●	●	●	●

2700 K / CRI 98 /SDCM 2		●									
3000 K	●	●	●	●	●	●	●	●	●	●	●
4000 K	●	●	●	●	●	●	●	●	●	●	●

CRI >80	●	●	●	●	●	●	●	●	●	●	●
CRI >90	●	●	●	●	●	●	●	●	●	●	●
SDCM 3	●	●	●	●	●	●	●	●	●	●	●

On/Off Standard	●	●	●	●	●	●	●	●	●	●	●
DALI/Phase-pulse	●	●	●	●	●	●	●	●	●	●	●
CLO	●	●	●	●	●	●	●	●		●	

Tilt 45° Turn 355°				Tunable White RGB/W Emergency	Tunable White Emergency	Tunable White RGB/W Emergency		Tunable White		Tunable White	Control Track
-----------------------	--	--	--	-------------------------------------	----------------------------	-------------------------------------	--	---------------	--	---------------	---------------